2019 Governor's Cup

Preshift Test Statement of Facts

1. The maximum 8 hour exposure level for carbon monoxide is _____ ppm. (MSHA 3028 P. 2-9)

- a. 20
- b. 30
- c. 50

2. Lubricating oil and grease kept underground shall be stored in fireproof, closed containers. (30 CFR 75.1104)

- a. Marked
- b. Metal
- c. Steel

All fire suppression devices shall be visually inspected at least once each
_____ by a person qualified to make such inspections. (30 CFR 75.1107-16(a))

- a. Week
- b. Month
- c. Shift

4. Preshift examinations are made by persons designated by the ______. (30 CFR 75.360(a)(1))

- a. Operator
- b. Owner
- c. Foreman
- 5. A bar for taking down loose______ shall be available in the working place or on all face equipment except haulage equipment. (30 CFR 75.211(d))
 - a. Rock
 - b. Slate
 - c. Material

- 6. The operator must establish 8-hour intervals of time ______ to the required preshift examinations. (30 CFR 75.360(a)(1))
 - a. Referring
 - b. Sustaining
 - c. Subject
- Any area of the mine where a hazardous condition is observed ______ be posted with a conspicuous danger sign where anyone entering the area would pass. (30 CFR 75.363(a))
 - a. Shall
 - b. Will
 - c. Must
- 8. Before implementing an approved revision to a roof control plan, all persons who are ______ by the revision shall be instructed in its provisions. (30 CFR 75.220(d))
 - a. Effected
 - b. Affected
 - c. Infected
- 9. Self-contained self-rescuers are used to protect the wearer from the ______of irrespirable atmosphere.
 - a. Affects
 - b. Effects
 - c. Aflicts
- - a. 50
 - b. 25
 - c. 100

2019 Governor's Cup

PRESHIFT TEST

ANSWER KEY

C
B
A
A
A
C
C
C
C
A
B
B
C