<u>2019</u>

Virginia Mining Institute

Preshift Test Statement of Facts

1.	Methane detectors should be calibrated with a known mixture at least once every 31 days. (30 CFR 75.320 (a))
	a. Methane
	b. Methane-oxygen
	c. Methane-air
2.	Afor taking down loose material shall be available in the working place or on all face equipment except haulage equipment. (30 CFR 75.211(d))
	a. Slate
	b. Bar
	c. Stick
3.	Rock dust applications to the roof, ribs, and floor shall be maintained to within
too	feet of the working face, except in those areas where the dust is too wet on high in incombustible content. (30 CFR 75.402)
	a. 20
	b. 40
	c. 25
4.	are used in mine ventilation to regulate airflow to meet the individual needs of each air split. (MSHA 3028 p. 3-12)
	a. Stoppings
	b. Check Curtains
	c. Regulators
5.	Damaged or other damaged belt conveyor components, which pose a fire hazard must be immediately repaired or replaced. (30 CFR 75.1731(a)
	a. Rollers
	b. Structure
	c. Belt

6.	shall be located within 1,000 feet from the nearest working ace and from the locations where mechanized mining equipment is being installed or removed. (30 CFR 75.1506(c)(1)	t
	. Refuse chambers . Refuge Alternatives . Intake Stopping Line	
7.	flame safety lamps may only be used as a supplementary testing device 30 CFR 75.320(d)	
	a. Antiqueb. Intrinsically Safec. Permissible	
8.	Velding, cutting and soldering with an arc or flame are prohibited withineet of a seal. (30 CFR 75.337(f)	
	. 150 b. 100 c. 25	
9.	The directional lifeline shall be equipped with one directional indicator cone ecurely attached to the lifeline, signifying the route of escape, placed at intervals not exceeding feet. (30 CFR 75.380(d)(7)(v)	
	. 150 b. 100 c. 25	
10.	shall be marked for identification. (30 CFR 75.904)	
	. Miners b. Tracking devices c. Circuit breakers	

2019 VMI

STATEMENTS OF FACT TEST ANSWER KEY

PRESHIFT CONTEST

- 1. C
- 2. B
- 3. B
- 4. C
- 5. A
- 6. B
- 7. C
- 8. A
- 9. B
- 10. C