Team	Name
1 Cuili	1401110

44		
₩		
11	 	_

## 2024 Harlan Co. Safety Day 1

<ol> <li>Before a fresh-air places between the</li> </ol>	base is old and new fresh-a	, gas test should be made in iir base.	all dead ends and high	
built		used	advanced	
		turns near the fire area to d	etermine if the mine	
atmosphere is pote	ntially explosive	,	checks	
readi	ngs	test	CHECKS	
3. The lower explos	sive limit for	4.0 percent.		
w ituus go	n	nydrogen	sulfide	
nitroge				
4. The lower explo	sive limit for	is 12.5 perce	ent.	
carbo	on dioxide	sulfur dioxide	carbon monoxide	
la.				
E Atoom is a unit	made up of working toward a common goal.			
		individuals	miners	
team	IS	IIIuiviuuais	,	

6 foar	n is an effective sealant w	nen used arour	d the perimeter of a seal.	
Expansion	Free		Urethane	<u>;</u>
7. Rescue Teams ma	y encounter many	while figh	ting fires directly by hand.	
hazards	ŀ	nour's	burns	
8. Overcasts are use circuiting to the ret		rrents to cross	without the intake air shor	t
certain		all		two
9. Before a rescue	eam goes, i	t will attend a b	oriefing session.	
outside		home	underg	round
10. Coking or	streamers, if encour	itered, should b	oe reported in location and	size.
sprite	co	ke	рер	osi