


iBRID™ MX6

Multi-Gas Monitor

■ The World's First Gas Monitor with a Full-Color Display



Get ready to see hazardous levels of oxygen, toxic and combustible gas, and volatile organic compounds (VOCs) like never before. The MX6 iBRID™ is more than an intelligent hybrid of Industrial Scientific's best monitoring technologies. It's the first gas monitor to feature a full-color LCD display screen.

The display improves safety with clear readings in low-light, bright-light or anywhere in between. Whether the work is outside, inside or underground, it's easy to see what gas hazards lurk in the

immediate work environment.

And a color display is more than eye-catching. It allows the user to step through instrument settings and functions with an intuitive menu and the instrument's five-way navigation button. It even supports the option of on-board graphing for easily interpreted direct readings and recorded data.

Plus, the MX6 iBRID is our most rugged instrument ever. It carries a lifetime warranty and is fully compatible with our DS2 Docking Station™ and iNet™ Instrument Network.

**INDUSTRIAL
SCIENTIFIC**

www.indsci.com




THE MX6 iBRID™ COLOR DISPLAY

Enhanced Visibility – Expanded Functionality




The MX6 clearly shows real-time readings in PPM or % by volume.



An intuitive menu provides easy access to features and setup.



Datalog trends and direct readings can be viewed graphically.



Calibration progress and results are shown for each sensor.




A "calibration due" warning appears for each relevant sensor.



Bright red numerals and a flashing backlight show alarm conditions.



Alarms shown with "Go/No Go" text and flashing backlight.



Color-coded text shows test or calibration results at a glance.

ACCESSORIES



DS2 DOCKING STATION™

- Stand-alone operation
- Link up to 100 IDS modules – dock thousands of instruments
- Automatic instrument calibration, record keeping, diagnostics and recharging
- Utilizes one central database
- Multilingual display
- iNet™ compatible

CHARGER / DATALINK



- Instantly download event logs and datalog data while instrument battery charges
- Quickly and easily configure instrument settings
- Also available – datalink only



- The aspirated version can remotely draw samples from a distance of 30.5 meters (100 feet).

ORDERING INFORMATION

| MX6 iBrid™ Part Number – MX6- ABCDEFGHIJ | | | |
|---|-----------------------|---------------|-------------------------|
| A-E (Common Configurations) | F | G | H |
| K1230 – LEL, CO, H ₂ S, O ₂ | 1 – Li-ion | 0 – Diffusion | 0 – English (No Manual) |
| K0230 – LEL, H ₂ S, O ₂ | 2 – Li-ion/Ext. Range | 1 – Pump | 1 – English |
| K1030 – LEL, CO, O ₂ | 3 – Alkaline | | 2 – French |
| K0030 – LEL, O ₂ | 4 – Li-ion MSHA/AUS | | 3 – Spanish |
| K123R – LEL, CO, H ₂ S, O ₂ , PID | 5 – Li-ion/Ext. Range | | 4 – German |
| K1235 – LEL, CO, H ₂ S, O ₂ , SO ₂ | MSHA/AUS | | 5 – Italian |
| K0235 – LEL, H ₂ S, O ₂ , SO ₂ | 6 – Alkaline MSHA/AUS | | 6 – Dutch |
| A-E (Common Industry Configurations) | | | 7 – Bahasa |
| KJ53R – LEL, CO/H ₂ S, O ₂ , SO ₂ , PID Petroleum Refining | | | 8 – Portugese |
| K103Q – LEL, CO, O ₂ , CO ₂ Brewing/Bottling/Wineries | | | |
| KJ538 – LEL, CO/H ₂ S, O ₂ , SO ₂ , ClO ₂ Pulp/Paper | | | |
| K673R – LEL, O ₂ , NH ₃ , Cl ₂ , PID HazMat | | | |
| M1030 – CH ₄ (%), CO, O ₂ Mining | | | |
| M143D – CH ₄ , CO, O ₂ , NO ₂ , NO Mining (Diesel Applications) | | | |

Build and price your MX6 online with the MX6 instrument builder.

www.indsci.com/MX6builder.asp

ACCESSORY ORDERING INFORMATION

| PART # | DESCRIPTION | PART # | DESCRIPTION |
|-----------------|--------------------------------------|------------|---------------------------------------|
| MX6KIT-K1230211 | Confined Space Kit, 4-gas w/Pump | 18107243 | MX6 Truck mount charger |
| MX6KIT-K123R211 | Confined Space Kit, 4-gas/PID w/Pump | 18107250 | MX6 Truck mount charger, hard-wired |
| 18106765 | SP6 Motorized Sampling Pump Module | 17131038-1 | Li-ion Battery Pack, UL/CSA/ATEX |
| 18107078 | Hand Aspirated Pump | 17131038-2 | Li-ion Ext. Battery Pack, UL/CSA/ATEX |
| 18106724-ABC+ | DS2 Docking Station™ for MX6 | 17131038-4 | Li-ion Battery Pack, MSHA/AUS |
| 18107086 | Datalink Assembly | 17131038-5 | Li-ion Ext. Battery Pack, MSHA/AUS |
| 18107094 | Battery Charger/Datalink, universal | 17131046-3 | Alkaline Battery Pack, UL/CSA/ATEX |
| 18107011 | Battery Charger, 12V | 18101046-6 | Alkaline Battery Pack, MSHA/AUS |
| 18107136 | Battery Charger, 5-Unit | 18106856 | Hard Leather Carrying Case, Diffusion |
| | | 18106880 | Hard Leather Carrying Case, Aspirated |

+ Ordering Information

A = Wireless Compact Flash (0 – none, 1 – installed +\$125.00)

B = number of iGas Readers at \$45.00 each

C = Power Cord (0 – US, 1 – UK, 2 – EU, 3 – AUS, 4 – ITA, 5 – DEN, 6 – SWZ)

Supplied with Monitor:

universal charger, nylon carrying case, belt clip, calibration cup, wrist strap, maintenance tool, manual, quick start guide, training CD, calibration tubing, dust filter/water stop (aspirated), calibration fitting (aspirated), sample tubing (aspirated).





Case Material:

Lexan/ABS/Stainless Steel w/protective rubber overmold

Dimensions:

135 mm x 77 mm x 43 mm (5.3" x 3.05" x 1.7") – diffusion version

Weight:

409 g (14.4 oz) typical

Display/Readout:

STN Color Graphic LCD

Sensors:

Combustible gas/Methane – Catalytic Diffusion/Infrared
Oxygen and Toxic gases – Electrochemical
CO₂ – Infrared
VOCs – Photolonization

Measuring Ranges:

Combustible Gases – 0 to 100% LEL in 1% increments
Methane – 0 to 5% of volume in 0.1% increments
(0 to 100% vol. optional)
Oxygen – 0 to 30% of volume in 0.1% increments
Carbon Monoxide – 0 to 999 ppm in 1 ppm increments
(0 to 9,999 ppm optional)
Hydrogen Sulfide – 0 to 500 ppm in 0.1 ppm increments
Hydrogen, Nitric Oxide – 0 to 999 ppm in 1 ppm increments
Chlorine – 0 to 99.9 ppm in 0.1 ppm increments
Nitrogen Dioxide, Sulfur Dioxide – 0 to 99.9 ppm in 0.1 ppm increments
Hydrogen Cyanide, Hydrogen Chloride – 0 to 30 ppm in 0.1 ppm increments
Ammonia – 0 to 200 ppm in 1 ppm increments
Chlorine Dioxide – 0 to 1 ppm in 0.01 ppm increments
Phosphine – 0 to 5 ppm in 0.01 ppm increments
(0 to 999 ppm optional)
Ethylene Oxide – 0 to 10 ppm in 0.1 ppm increments
Carbon Dioxide – 0 to 5% of volume in 0.1% increments
VOCs (general) – 0 to 2,000 ppm in 0.1 increments

Operating Temperature Range:

-20°C to 55°C (-4°F to 131°F) typical

Operating Humidity Range:

15% to 95% non-condensing (continuous) typical

Power Source/Run Times:

Rechargeable Lithium-ion (Li-ion) Battery Pack (24 hours typical)
Rechargeable, Extended-Range Lithium-ion (Li-ion) Battery Pack
(36 hours typical)
Replaceable AA Alkaline Battery Pack (10.5 hours typical)

Certifications:

IECEX/ATEX: Intrinsic Safety: EEx ia d IIC T4
Equipment Group and Category: II 2G
UL: Class I, Groups A,B,C,D T4; AEx ia d IIC T4
CSA: Class I, Groups A,B,C,D T4 (pending)
MSHA: CFR30, Part 18 and 22,
Intrinsically safe for methane/air mixtures (pending)

INDUSTRIAL SCIENTIFIC CORPORATION

CORPORATE HEADQUARTERS

1001 Oakdale Road • Oakdale, PA • 15071-1500 • USA

www.indsci.com



AMERICAS

Tel.: +1-412-788-4353
Fax: +1-412-788-8353
info@indsci.com

ASIA PACIFIC

Tel.: 86-10-8497-3970
Fax: 86-10-8497-3971
sales@isc-cn.com

EUROPE

Tel.: 33-3-21-60-80-80
Fax: 33-3-21-60-80-00
info@groupoldham.com

AUSTRALIA / NZ

Tel.: +61-2-8870-3400

GERMANY

Tel.: +49-231 / 9241-0

MIDDLE EAST

Tel.: +971-50-455-8518

SINGAPORE

Tel.: +65-6561-7377

UNITED KINGDOM

Tel.: +44-0-1782-562002

CZECH REPUBLIC

Tel.: +420-234-622-222/3

ITALY

Tel.: +39-011-3801371

NETHERLANDS

Tel.: +31-76-5427-609

SWITZERLAND

Tel.: +41-26-652-51-18